

PT 51

Features

- 15" PCAP Touchscreen
- IP54 Water and Dust Resistant Front Panel
- Intel Bay Trail Processor (Fanless design)
- 3 Track MSR Available
- VESA Mount Compliant
- 2nd 15" Display and Customer Display Available




Application



The state-of-the art of PT51 present stylish and modern design POS system. The cutting edge of mechanical design such as hidden cable and hidden power adapter are space saving and easy to manage counter space. The fanless design PT51 guarantees stability and high performance to enhance customer experience. Seamless integration of various peripheral modules such as MSR, Second Display and Customer Display are available to meet all customer requirement.

Specification

System	Motherboard Processor Chipset System Memory Storage Device Graphic Engine	MB-36 Intel Bay Trail CPU Celeron J1900, up to 2.4GHz CPU Integrated 1 x DDR3L SO-DIMM up to 8GB 1 x 64 GB SSD (M.2. B) Intel HD Graphic DX11 and OCL1.1
LCD Touch Panel	LCD Size Brightness Resolution Touch Screen	15" TFT LCD 300 nits 1024 x 768 True-Flat PCAP Multi-touch
Expansion	Mini PCI-E Slot M.2 .B Slot	1 1
External I/O Ports	USB Serial Port LAN Cash Drawer VGA DC Jack Power Button	1 x USB3.0, 7 x USB 2.0 1 x DB-9 (COM1) 1 x RJ-45 (10/100/1000 baseT) 1 x RJ-11 (2 In / 2 Out) 1 x DB-15 1 x 2-pin 1
Optional I/O	Serial Port	2 x DB-9 (COM2-3)
Audio	Internal Speaker	1 x 2W (Option)
Indicator	Power LED	1
Power	Power Adapter	60W / 12V
Peripheral (Option)	MSR Customer Display 2nd Display	3-Track MSR (USB) LCM display 2 x 20 characters (USB) 15.1" / 300 nits / 1024 x 768 (VGA)
Mounting (Option)		VESA Mount 75 x75 / 100 x 100 mm
Certificate	EMC & Safety	BSMI/CCC/CE/FCC Class A / ESD: Air 8kV ; Con 4kV/ LVD
Environment	Operating Temperature Storage Temperature Humidity	0°C ~ 35°C (32°F ~ 95°F) -20°C ~ 60°C (-4°F ~ 140°F) 20% ~ 80% RH non-condensing
Dimensions (WxDxH)		360 x 199 x 330 mm
Weight		5.01 kgs
OS Supported		Windows 7, POSReady 7, Windows Embedded 8.1 Industry, Windows 10 IoT, Linux



Tel: 86-755-2733 7509
Fax: 86-755-2733 7931
www.wimisis.com

E-mail: sales@wimisis.com
Address: Room 3A01, Floor 3A, Building A, Tongxin Technology Mansion,
Qiaotou Community, Fuhai Street, Baoan District, Shenzhen 518103, China