

Line Thermal Printer



WP-T810

Printing speed : 220 mm/s

Interface : Built-in USB / RS-232C, Parallel, Bluetooth and Ethernet are optional



Barcord POS/ECR Gas-Pos



White



Black

Interface Cards



RS-232

Parallel

Ethernet

Bluetooth

Accessory



58 mm paper separator

Specification

Model	WP-T810		
Printing method	Thermal line		
Printing speed	220 mm/s		
Command	ESC/POS		
Driver	Linux, Windows and OPOS		
Character structure	Alphanumeric (Font A)	Alphanumeric (Font B)	Kanji
	12 x 24	9 x 17	24 x 24
Columns	80mm / 58mm	48 columns / 34 columns	64 columns / 45 columns
Character size		24 columns / 17 columns	24 columns / 17 columns
		1.50 (W) x 3.00 (H)	1.13 (W) x 2.13 (H)
Density	203dpi		
Fonts	Multilingual code page x 40, Chinese, Japanese, Thai, Korean, Others		
Bar code	UPC-A, UPC-E, EAN13, EAN8, Code39, Code93, CODABAR, Code128, ITF, QR Code		
Detectors	Paper end, Paper near end, Cover, Printer head overheat and Cutter jam		
Paper	Single-ply thermal paper roll		
Paper roll size	79.5±0.5 (W) x 83 mm (Dia.)		
Paper thickness	0.05 ~ 0.06 mm		
Drawer output	2		
Reliability	Head	100 km or more	
	Cutter	700,000 times	
Memory	Buffer	4K bytes	
	SRAM	256K bytes	
	Flash	1M bytes (NV Image)	
Power supply	+24 VDC / 2.5 A		
Interface	Built-in USB / RS-232C, Parallel and Ethernet are optional		
Bluetooth feature	On board Bluetooth 3.0+EDR and Bluetooth 4.0 stack		
	Class 2 transmitter, +2dBm typical		
Gross weight	2.40 kg		
External dimension	136 (W) x 178 (D) x 123 (H) mm		
Temperature	Operating	0 ~ 45°C	
	Storage	-10 ~ 50°C	
Humidity	Operating	10 ~ 90 %RH	
	Storage	10 ~ 90 %RH	