



## K730 SERIES

New Ultra-slim Panel PC



POS Stand

Printer Stand

Floor Stand


### FEATURES

- Multiple widescreen options- 11.6"/15.6"/18.5"/21.5"
- Transformable stands- POS/Printer/Floor stand
- Flexible 4-sided peripherals- Fingerprint/2D scanner/NFC/MSR
- Aesthetic design- Narrow bezel display
- Modular design - Easy maintenance

A. Screen Sizes



B. Modularized 4-sided Peripheral



	Motherboard	F14	D84U	F34	F84U
System	Processor	Qualcomm® 450	Intel® Kaby Lake 3965U Intel® Kaby Lake i3-7020U	Intel® Elkhart Lake Celeron J6412	Intel® Tiger Lake i3-1115G4
	Memory	3GB LPDDR3	4GB DDR4	4GB DDR4	4GB DDR4
	Storage	32GB eMMC	128GB SSD (M.2)	128GB SSD (M.2)	128GB SSD (M.2)
	Supported OS	Android 9.0	Windows 10 IoT Enterprise, Linux	Windows 10 IoT Enterprise, Linux	Windows 10 IoT Enterprise, Linux
I/O Ports	USB Type-A	2x USB3.0 2x USB2.0	2x USB3.0 2x USB2.0	2x USB3.0 2x USB2.0	2x USB3.0 2x USB2.0
	USB Type-C (data only)	1x USB3.0	2x USB3.0	2x USB3.0	2x USB3.0
	Serial Port	2x DB9 (Powered RS232) (default: 0V; COM1/COM2: 0V, 5V, 12V)			
	LAN	1x RJ45			
	Cash Drawer	1x RJ11			
	FeDP	K736: 1x Flytech Proprietary miniDP K737, K738, K739: 2x Flytech Proprietary miniDP			
	DC Jack	1x 4PIN (with latch)			
Display	Size and Resolution	K736: 11.6" 1920 x 1080 K737: 15.6" 1920 x 1080 K738: 18.5" 1366 x 768 K739: 21.5" 1920 x 1080			
	Touch Screen	True-Flat PCAP multi-touch			
Audio	Speaker	1x 3W			
Power	Power Supply	65W / 19V	120W / 19V	65W / 19V	120W / 19V
Certificate	EMC & Safety	FCC Class A, CE Mark Class A, LVD			
Environment	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)			
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)			
	Humidity	20% ~ 85% RH non-condensing			
Dimensions	W x D x H	K736: 277 x 180.5 x 40.8 mm (10.9" x 7.1" x 1.6") K737: 370 x 235 x 42.3 mm (14.6" x 9.3" x 1.7") K738: 453 x 273 x 50.2 mm (17.8" x 10.8" x 2") K739: 518 x 310 x 49.3 mm (20.4" x 12.2" x 1.9")			
Weight	Weight	K736: 1.4 kg (3.1 lbs) K737: 3.0 kg (6.6 lbs) K738: 4.4 kg (9.7 lbs) K739: 5.3 kg (11.7 lbs)			
Mounting	VESA Mount	K736: 75 x 75 K737, K738, K739: 75 x 75 / 100 x 100			
Options	Wireless LAN + BT	BT4.1 WiFi 802.11 a/b/g/n/ac (*built-in on F14 motherboard)	K736: M.2 WiFi/BT Module K737, K738, K739: WiFi+BT USB dongle		
	POE	POE module 802.3bt Type 3 (up to 60W)	-	-	-
	MSR	3-Track MSR			
	Fingerprint	Fingerprint Reader			
	NFC	-	NFC Reader		
	Scanner	2D Scanner			
	Camera	5MP Camera (with microphone)			
	Pin Pad	Supported Verifone® P400/VX805/VX820, Ingenico iPP 350/320, LANE 3000			
	Cable	Converter cable for FeDP to VGA Converter cable for FeDP to HDMI			
	Light Bar	Light Bar Module			
	Stand	POS Stand, Printer Stand, Floor Stand			
	Printer Kit	Epson® TM-m30/TM-T88VI, Star TSP-654/TSP-100/mc-Print3, Xprinter XP-R330H			