

# FLYTECH

POS

Build Smart Solutions for Tomorrow

## POS 8000



### Application Benefits :

- Multipurpose Embedded Box PC
- Wall/Desk Mount Brackets Available
- Easy Serviceability and Upgradability



Flytech's POS 8000 is a powerful compact embedded Box PC built with a die-casting front cover and impact-resistant top and bottom covers. The space-saving and design make this unit a great fit for any environment and an easy way for system maintenance. It is equipped with an Intel Bay Trail or Haswell processor and offers sufficient I/O ports for various peripheral connectivity. Fanless\* and Low-power consumption\* make the POS 8000 an excellent choice for any type of business looking for a complete and cost-effective embedded Box PC solution.

## Features


- Intel Bay Trail or Haswell Processor
- Fanless\* and Slim
- Die-Casting Front Cover and Metal Top & Bottom Covers
- Easy Maintenance and Service
- Rich I/O Ports for Various Peripherals
- Wall or Desk Mount Brackets Available

\*Fanless and Low Power Consumption are Available for Intel Bay Trail


## Specification

System	Motherboard	D36*	D66
Processor	Intel Bay Trail CPU Celeron J1900 2.4GHz		Intel Haswell CPU LGA-1150
Chipset	CPU Integrated		Intel Lynx Point PCH H81
System Memory	1x DDR3L 1066/1333MHz SO-DIMM up to 8GB		1x DDR3 1333/1600MHz SO-DIMM up to 8GB
Storage Device	1x 2.5" SATA HDD or SSD or SSD module		1x 2.5" SATA HDD/SSD or 2x 2.5" SATA HDD
Graphic Engine	Intel HD Graphics DX11 and OCL1.1		Intel HD Graphics DX11.1 and OCL1.2
<b>External I/O Ports</b>	<b>USB</b>	1x USB3.0, 5x USB2.0	2x USB3.0, 6x USB2.0, 1x USB2.0 at front
	<b>Serial Port</b>	4 (COM1/2/3 powered RS232) (3x RJ45: default 0V; COM1,COM2 0V/5V; COM3 0V/12V; 1x DB9: COM4 w/o power)	4 (COM1/2/3 powered RS232) (3x RJ45: default 0V; COM1,COM2 0V/5V; COM3 0V/12V; 1x DB9: COM4 w/o power)
	<b>LAN</b>	1x RJ45	1x RJ45
	<b>Cash Drawer</b>	1x RJ11 (12V/24V)	1x RJ11 (12V/24V)
	<b>Parallel Port</b>	1 (Option)	1 (Option)
	<b>VGA</b>	1x DB15	1x DB15
	<b>Display Port</b>	1	1
	<b>Audio Line-out</b>	1	1
	<b>DC Jack</b>	1x 4 pin w/ lock	1x 4 pin w/ lock
	<b>PS/2</b>	N/A	1
	<b>Kensington Lock</b>	1	1
<b>Option</b>	<b>Powered USB + LAN</b>	N/A	3x Powered USB (1x 24V, 2x 12V), 1x 2nd LAN, DC-24V out
	<b>Wall Mount Kit</b>	1 (Option)	1 (Option)
<b>Control / Indicator</b>	<b>Power Button</b>	1	1
	<b>LED Indicator</b>	1	1
<b>Power</b>	<b>Power Supply</b>	65W / 19V	120W / 19V
<b>Communication</b>	<b>Wireless LAN</b>	802.11 b/g/n WLAN card & antenna (Option) (Choose either Wireless LAN or 2nd LAN)	802.11 b/g/n WLAN card & antenna (Option) (Choose either Wireless LAN or 2nd LAN)
<b>Certificate</b>	<b>EMC &amp; Safety</b>	FCC Class A, CE Mark, LVD	FCC Class A, CE Mark, LVD
<b>Environment</b>	<b>Operating Temperature</b>	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)
	<b>Storage Temperature</b>	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	<b>Humidity</b>	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
<b>Dimensions (WxDxH)</b>		270 x 220 x 50 mm (10.6" x 8.7" x 2.0")	270 x 220 x 50 mm (10.6" x 8.7" x 2.0")
<b>Weight</b>		1.9 kg (4.2 lbs)	2.9 kg (6.4 lbs)
<b>OS Supported</b>		Windows 7, POSReady 7, Windows Embedded 8.1 Industry, Windows 10 IoT Enterprise (D66: 64bit), Linux	

D66 Front



D66 Rear W/ PWR USB



### Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,  
Taipei City 11494, Taiwan, R.O.C.  
Tel: 886-2-8791-4988  
Fax: 886-2-8791-4966  
E-mail: sales@flytech.com.tw  
www.flytech.com

### U.S.A. - California

271 East Brokaw Road, San Jose,  
CA 95112, U.S.A.  
Tel: 1-510-257-5180  
Fax: 1-510-257-5181  
E-mail: sales@flytech.com

### China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555  
Fax: 86-21-5426-1001  
E-mail: sales@flytech.com.cn  
www.flytech.com.cn

### China - Hong Kong SAR

Room 01, 6/F, Block A, Tonic Industrial  
Centre, 26 Kai Cheung Road, Kowloon  
Bay, Kowloon, Hong Kong  
Tel: 852-3525-5800  
Fax: 852-2751-7447  
E-mail: sales@flytech.com.hk