

Kiosk Thermal Printer



WP-K651

Printing speed : 70 mm/s

Interface : Built-in USB and RS-232C



Specification

Model	WP-K651		
Printing method	Thermal line		
Printing speed	70 mm/s		
Command	ESC/POS		
Driver	Linux, Windows, OPOS, JavaPOS and Android SDK		
Character structure	Alphanumeric (Font A)	Alphanumeric (Font B)	Kanji
	12 x 24	9 x 17	24 x 24
Number of columns	32 columns	42 columns	16 columns
Character size	1.50 (W) x 3.00 (H)	1.13 (W) x 2.13 (H)	3.00 (W) x 3.00 (H)
Density	203dpi		
Fonts	Multilingual code page x 46, Chinese, Japanese, Thai, Korean, Unicode		
Bar code	UPC-A, UPC-E, EAN13, EAN8, CODE39, CODE93, CODABAR, CODE128, ITF, QR Code		
Detectors	Paper end, Paper near end, Printer head open, overheat, cutter jam and paper out.		
Paper	Single-ply thermal paper roll		
Paper roll size	57.5±0.5 (W) x 80 mm (Dia.)		
Paper thickness	0.05 ~ 0.06 mm		
Solenoid output	1		
Reliability	Head	50 km	
	Cutter	1,000,000 times	
Memory	Buffer	4K bytes	
	SRAM	128K bytes	
	Flash	1M bytes (NV image)	
Power supply	+12 VDC / 3 A		
Interface	Built-in USB and RS-232C		
Weight	792 g		
External dimension	130 (W) x 153 (D) x 113 (H) mm		
Temperature	Operating	0 ~ 45°C	
	Storage	-20 ~ 60°C	
Humidity	Operating	10 ~ 90 %RH	
	Storage	10 ~ 90 %RH	