



Thermal Receipt Printer


CP-Q4BUT

- Wall mount available;
- Support 58/80 switch
- Support IAP update online
- Support QRcode, PDF417
- Transparent cover design
- Support UberEat and FoodPanda



CP-Q4BUT

Thermal Receipt Printer



Model	CP-Q4BUT
Printing method	Direct thermal
Paper width	57.5±0.5mm / 79.5±0.5mm
Print width	72mm (Optional:58/80mm)
Column capacity	576 dots/line or 512 dots/line
Printing speed	230 mm/s
Interface	USB+Bluetooth
Character size	3.75mm (Adjustable by commands)
Line spacing	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns
Column number	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) /PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew /East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	200 K bytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 110~240V, 50 ~ 60Hz, Output: DC 24V/2.5A
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	1.0 Kg
Dimensions	189.15*145.35*139.7mm(D*W*H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150Km
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/OPOS/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows

