

## Specifications of M354 Series (8" LCD Monitor)

Spec	M354ND	M354NC	M354RD	M354RC
General Description	VGA, Non-touch	USB, Non-touch	VGA, Touch	USB, Touch
Display Size	8"			
Standard Cabinet Color	Black			
Optimal Resolution	800 * 600			
Panel Brightness	350 cd/m <sup>2</sup> (typ)			
Contrast Ratio	500:1(typ)			
Response Time	25 ms (typ)			
LCD Viewing Angle(L / R / U / D)	70 / 70 / 50 / 70			
Input Video Signal	VGA (mini-DIN 8 pins)	USB B Type	VGA (mini-DIN 8 pins)	USB B Type
Touch Function	N/A	N/A	5W Resistive Touch (USB)	5W Resistive Touch (USB)
Power consumption	6 W	2.5 W	6 W	2.5 W
Input Frequency	Horizontal: 31.5-60.2 kHz ; Vertical : 56.3Hz~75Hz			
Power supply	DC 12V±10%	DC 5V±10%	DC 12V±10%	DC 5V±10%
Temperature	Operating : 0°C~40°C ; Storage : -10°C~50°C			
Humidity	Operating : 20%~80% ; Storage : 10%~90%			
Weight	0.7 kg (approx.)			
Physical Dimension	L202*H163*W35.46 mm			
Approvals	CE, FCC			
Wall Mount Screw Holes	VESA 75 * 75 mm			



Optional Aluminum Stand



Optional Pole Base

