

# JS-903

手持式 2D 影像條碼掃描器  
Handheld 2D Barcode Scanner

## 物理特性/Physical Characteristics

尺寸 Dimensions : 97.00mm x 62.8mm x 162.70mm

電壓 Voltage : 5V

待機電流 Stand-by Current : 250mA

重量 Weight : 115.5g

開機電流 Starting Current : 355mA

工作電流 Work Current : 400mA

## 性能指標/Performance Characteristics

感測器圖元 Image (Pixels) : 640 pixels (H) x 480 pixels (V)

光源 Light Source : (Aimer) Red color LED; (Illumination) White color LED

視場角 Field of View : 37°(H) , 28°(V)

旋轉傾斜偏轉 Roll / Pitch / Yaw : 360° , ±65° , ±65°

列印對比度 Print Contrast : 20% minimum reflective difference

介面支援 Interfaces Supported : USB

運動容差 Motion Tolerances : 40cm/s



## 解碼能力/Symbology Decode Capability

一維條碼 1-D: Codabar、Code 39、Code 32 Pharmaceutical (PARAF)、Interleaved 2 of 5、NEC 2 of 5、Code 93、Straight 2 of 5 Industrial、Straight 2 of 5 IATA、Matrix 2 of 5、Code 11、Code 128、GS1-128、UPC-A、UPC-E、EAN/JAN-8、EAN/JAN-13、MSI、GS1 DataBar Omnidirectional、GS1 DataBar Limited、GS1 DataBar Expanded、China Post(Hong Kong 2 of 5)、Korea Post.

二維條碼 2-D: Codeblock A、Codeblock F、PDF417、Micro PDF417、GS1 Composite Codes、QR Code、Data Matrix、MaxiCode、Aztec、HANXIN.

## 用戶環境參數/User Environment

工作溫度 Operating Temperature : -20°C to 60°C

存儲溫度 Storage Temperature : -30°C to 70°C

濕度 Humidity : 5% to 95% relative humidity, non-condensing

抗震性 Shock Specifications : Designed to withstand 1.2m(5') drops

環境光免疫 Ambient Light Immunity : 0-100,000 Lux.

## 解碼範圍/Decode Ranges

Code39(5mil) : 30-80mm

Code39(13mil) : 45-180mm

QR(20mil) : 25-200mm

Performance may be impacted by bar code quality and environmental conditions

