

		BSC10II-UE	BSC10II-U
Interface		USB-C x 1	USB-C x 1
		USB-A x 1	-
		Ethernet x 1	-
		DK-Port x 1	DK-Port x 1
Printer Method		Direct Thermal Line Printing	
Print Speed		Up to 250 mm/second	
Resolution		203dpi	
Emulation		StarPRNT or ESC/POS	
Body Color		Dark Gray Only	
Installation		Horizontal, Vertical or Wall-mount	
Paper Specifications	Type	Thermal Paper Roll	
	Print Width	80mm / 58mm (Using Paper Guide)	
	Roll Diameter	Max. ϕ 83mm	
	Thickness	49-85 μ m	
	Top Margin	11mm	
Auto-cutter	Type	Guillotine type	
	Cutting Method	Partial cut (Leave center point)	
	Life	2 million cuts	
Sensors		Paper End, Cover Open	
Power Supply		Internal with Power Cable included 100-240V AC $\pm$ 10%	
Reliability		60 million lines (MCBF)	
Dimensions		140×169×119 mm (W×D×H)	
Weight		Approx. 1.3 kg (without paper roll)	
Accessories included in the box		Power Cable, Rubber feet 2pcs, Paper Guide	
Options		Buzzer (BU01-24-A)	

