



CP-Q4+

# CP-Q4+

80mm Width w/Auto-Cutter

USB + LAN

**Fresh Look and Compact Designed Thermal Printer with High Performance**



### 1. Need for speed and space-saving

To meet the current digital transformation, the customers more concerned about the speed and space-saving for their applications. CP-Q4+ is designed to have 260mm/second printing speed, and very small foot printing mechanism.



### 2. Enjoy the high performance of printing

CP-Q4+ supports most of 1D or even QR code and PDF417 printing. Furthermore support the easy paper-loading, wall mounting, OPOS drivers and excellent printing performance.



### 3. 3-in-1 interface and user-friendly

CP-Q4+ supports USB + LAN as standard for your applications. The 3-in-1 interface device is very helpful for your application. The customer can have CP-Q4+ for most of the computer connections.

### 4. Bright idea of “ paper see-through” cover

Besides the very cute top cover design, CP-Q4+ has the line-bar paper see-through design on the cover, which is helpful to see the paper roll status.



## Technical Specifications

### Model Numbers CP-Q4+

Printing	
Printing method	Direct thermal
Print width	79.5 ± 0.5mm / 57.5 ± 0.5mm
Column capacity	576 dots/line 512 dots/line
Printing speed	260mm/s
Interface	USB+LAN
Printing area	72mm
Maximum paper diameter	Φ80mm
Paper thickness	0.06~0.08mm
Character size	3.75mm (changeable by commands)
Command	Compatible with ESC/POS
Column number	ANK, Font A : 12x24 dots Font B : 9x17 dots Simplified Chinese / Traditional Chinese: 24x24 dots
Cutter	
Auto cutter	Partial
Barcode Character	
Code Page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、 PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、 WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、 Latvian、Arabic、PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/ CODE128/QR CODE/PDF417
Buffer	
Input buffer	128K Bytes
NV Flash	256k bytes
Power	
Power adaptor	Input : AC 110V/240V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Gross Weight	1.0KG
Dimensions	189.15×145.35×139.7mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45°C) humidity(10~80RH%)
Storage environment	Temperature(-10~60°C) humidity(10~90RH%)
Reliability MAX	
Cutter life	1.5 million cuts
Printer head life	150KM
Operating system	
Windows / Linux / JPOS / Android	



Birch is a trademark of Birch Technology

All other products, brands or companies are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details