

Series	mC-Print3	
Model Name	MCP31CI	
Interface	USB-Cx1 Up to 20W(for iOS/Android/PC connection)	
	USB-Ax1 (for peripheral / external hub connection)	
	Ethernet x 1	
	DK-Port x 1 for cash drawer	
Body Color	White / Black	
Installation	Horizontal (Front exit only)	
Emulation	StarPRNT™	
Print Speed	Up to 400 mm/sec	
Paper Specifications	Type	Thermal paper roll
	Print Width	80mm / 58mm (Using Paper Guide)
	Roll diameter	φ 83mm max.
	Thickness	49~75μm
Head	Method	Direct Thermal Line Printing
	Resolution	203dpi
	Life Span	200km
Auto cutter	Type	Guillotine
	Cutting Method	Partial cut (Leave center point)
	Life Span	2,000,000 cuts (Recommended paper)
Sensor	Cover Open , Paper End , Near End	
Paper transport function	Top margin 2mm min. (default 11mm) , Decurl function	
Power Supply	DC24V±10%	
Dimensions	132 x 140 x 125mm (WxDxH)	
Weight	Approx. 1.3 kg (without roll paper)	
Dimensions of package	213x213x215mm (WxDxH)	
AC Adapter	PS65AT-24A	
Accessories included in the box	AC Adaptor , Power Cable , Safety sheet , Setup sheet	
Options	Paper Guide for 58mm paper roll , USB-A to C cable for PC Connection , Wall Mounting Kit (WB-MC30) , Barcode Scanner (BCR-POP1) , Customer Display (SCD222U) , Buzzer(BU01-24-A) , Melody Speaker (mC-Sound) , Wireless LAN Unit (MCW10)	